



## LESS TIME

Faster flow — using less propane means more profit for you; get the job done quick and right.

## MORE PERFORMANCE

Feel confident knowing Johns Manville consistently delivers high quality APP membranes with the same toughness, the same installation efficiencies and the same quality results.

## LET'S GET TO WORK

From a company you can trust with more than 150 years of roofing system expertise and integrity.

## APP MODIFIED BITUMEN MEMBRANE SELECTOR GUIDE

| Product                             | Use  |     |     |          | Reinforcement |           |           | Application   |           | ASTM                    | Size               |
|-------------------------------------|------|-----|-----|----------|---------------|-----------|-----------|---------------|-----------|-------------------------|--------------------|
|                                     | Base | Ply | Cap | Flashing | Fiber Glass   | Polyester | Composite | Cold Adhesive | Heat Weld |                         |                    |
| <a href="#">JM APP™ Base 2.0 SQ</a> | X    | X   |     |          | X             |           |           |               | X         | D 6509                  | 200 ft² (18.58 m²) |
| <a href="#">JM APP™ Base</a>        | X    | X   |     |          | X             |           |           | X             | X         | D 6509                  | 150 ft² (13.93 m²) |
| <a href="#">JM APP™ Base Plus</a>   | X    | X   |     |          | X             |           |           | X             | X         | D 6509                  | 150 ft² (13.93 m²) |
| <a href="#">APPeX® 4S</a>           |      | X   | X   | X        |               | X         |           |               | X         | D 6222 Type I, Grade S  | 100 ft² (9.29 m²)  |
| <a href="#">APPeX® 4.5M</a>         |      |     | X   | X        |               | X         |           |               | X         | D 6222 Type I, Grade G  | 100 ft² (9.29 m²)  |
| <a href="#">APPeX® 4.5M CR G</a>    |      |     | X   | X        |               | X         |           |               | X         | D 6222 Type I, Grade G  | 100 ft² (9.29 m²)  |
| <a href="#">APPeX® 4.5M FR</a>      |      |     | X   | X        |               | X         |           |               | X         | D 6222 Type I, Grade G  | 100 ft² (9.29 m²)  |
| <a href="#">APPeX® 4.5M FR CR G</a> |      |     | X   | X        |               | X         |           |               | X         | D 6222 Type I, Grade G  | 100 ft² (9.29 m²)  |
| <a href="#">BICOR™ S</a>            | X    | X   |     |          |               |           | X         | X             | X         | D 6223 Type I, Grade S  | 100 ft² (9.29 m²)  |
| <a href="#">BICOR™ M FR</a>         |      |     | X   | X        |               |           | X         | X             | X         | D 6223 Type I, Grade G  | 100 ft² (9.29 m²)  |
| <a href="#">TRICOR™ S</a>           | X    | X   |     |          |               |           | X         | X             | X         | D 6223 Type II, Grade S | 100 ft² (9.29 m²)  |
| <a href="#">TRICOR™ M FR</a>        |      |     | X   | X        |               |           | X         | X             | X         | D 6223 Type II, Grade G | 100 ft² (9.29 m²)  |
| <a href="#">TRICOR™ M FR CR G</a>   |      |     | X   | X        |               |           | X         | X             | X         | D 6223 Type II, Grade G | 100 ft² (9.29 m²)  |
| <a href="#">TRICOR™ M FR CR</a>     |      |     | X   | X        |               |           | X         | X             | X         | D 6223 Type II, Grade G | 100 ft² (9.29 m²)  |
| <a href="#">ValuWeld S</a>          |      | X   | X   | X        |               | X         |           |               | X         | -                       | 100 ft² (9.29 m²)  |
| <a href="#">ValuWeld G</a>          |      |     | X   | X        |               | X         |           |               | X         | -                       | 100 ft² (9.29 m²)  |

## COATINGS SELECTOR GUIDE

| Product  | Use                            | Description  | Size                   | Standard                              |
|--|--------------------------------|--|------------------------|---------------------------------------|
| <a href="#">Fibrated Aluminum Roof Coating</a> | Protective, reflective coating | A highly reflective coating made of pure aluminum pigment flakes blended with selected, refined solvents and reinforcing fibers for heavy-duty service used as a protective, reflective coating. | 4.75 gal (17.9 l) pail | ASTM D 2824, Type III (Asbestos Free) |

## ACCESSORY SELECTOR GUIDE

| Product                             | Use   | Description   | Size                |
|-------------------------------------|---|---|---------------------|
| <a href="#">CR Seam Coating</a>     | Asphalt bleed-out coverage or aesthetic touch ups | 100 percent acrylic elastomeric coating with unique bleed-blocking properties particularly well suited for coating over asphalt surfaces. | 5 gal (18.9 l) pail |
| <a href="#">CR Roofing Granules</a> | Reflective Roofing Granules                       | Bright white granules specifically designed for high reflectivity and durability  | 41 lb. pail         |

## COVER BOARD SELECTOR GUIDE

| Product                    | Use         | Description  | Size                    | Standard   |
|----------------------------|-------------|--|-------------------------|------------|
| <a href="#">DuraBoard®</a> | Cover Board | A perlite-based cover board, the top surface is sealed with a polymerized asphalt emulsion to allow heat welding applications. | 1/2"-1" (13 mm - 25 mm) | ASTM C 728 |